PHYSICS **0625/53**

Paper 5 Practical Test **May/June 2019**

MARK SCHEME

Maximum Mark: 40

Published

This document consists of **7** printed pages.

PUBLISHED
Generic Marking Principles

These general marking principles must be applied by all examiners when marking candidate answers. They should be applied alongside the specific content of the mark scheme or generic level descriptors for a question. Each question paper and mark scheme will also comply with these marking principles.

GENERIC MARKING PRINCIPLE 1:

Marks must be awarded in line with:

- the specific content of the mark scheme or the generic level descriptors for the question
- the specific skills defined in the mark scheme or in the generic level descriptors for the question
- the standard of response required by a candidate as exemplified by the standardisation scripts.

GENERIC MARKING PRINCIPLE 2:

Marks awarded are always **whole marks** (not half marks, or other fractions).

GENERIC MARKING PRINCIPLE 3:

Marks must be awarded **positively**:

- marks are awarded for correct/valid answers, as defined in the mark scheme. However, credit is given for valid answers which go beyond the scope of the syllabus and mark scheme, referring to your Team Leader as appropriate
- marks are awarded when candidates clearly demonstrate what they know and can do
- marks are not deducted for errors
- marks are not deducted for omissions
- answers should only be judged on the quality of spelling, punctuation and grammar when these features are specifically assessed by the question as indicated by the mark scheme. The meaning, however, should be unambiguous.

GENERIC MARKING PRINCIPLE 4:

Rules must be applied consistently e.g. in situations where candidates have not followed instructions or in the application of generic level descriptors.

GENERIC MARKING PRINCIPLE 5:

Marks should be awarded using the full range of marks defined in the mark scheme for the question (however; the use of the full mark range may be limited according to the quality of the candidate responses seen).

GENERIC MARKING PRINCIPLE 6:

Marks awarded are based solely on the requirements as defined in the mark scheme. Marks should not be awarded with grade thresholds or grade descriptors in mind.

Question	Answer	Marks
1(a)	5 *b* values decreasing	**1**
	all < 75.0 cm <u>and</u> recorded to at least 1 dp	**1**
1(b)	graph:	
	axes labelled correct orientation, with quantity and unit	**1**
	appropriate scales (plots occupying at least ½ grid)	**1**
	plots all correct to less than ½ small square and precise plots	**1**
	well-judged line <u>and</u> thin line	**1**
1(c)(i)	*G* present <u>and</u> triangle method seen on graph	**1**
1(c)(ii)	M_U in range 70.0 to 130.0 (g)	**1**
	2/3 sig figs and unit	**1**
1(d)	(difficult to see centre of block) and valid method, e.g. • (measure width of block and) add ½ width to 5.0 cm to find position for edge of block • mean value of marks at both edges of mass • mark centre line of mass and align with mark on rule	**1**
1(e)	move block back and forth to find the point of balance / owtte	**1**

Question	Answer	Marks
2(a)	sensible value for θ_R	1
2(b)	θ_C increasing	1
	θ_H decreasing	1
	θ_H decreasing more slowly than θ_C increasing	1
2(c)	s, °C, °C, °C – all correct	1
	30, 60, 90, 120, 150, 180	1
2(d)(i)	between θ_H at 180 s and halfway between θ_H and θ_C at 180 s	1
	justification with reference to hot and cold water trends	1
2(d)(ii)	θ_R / room temperature	1
2(e)	any **two** from: • thinner walls on tube • metal tube • bung/lid on tube • insulate sides of beaker/lid on beaker • higher <u>initial</u> hot water temperature • lower <u>initial</u> cold water temperature • increase volume of hot water • decrease volume of cold water • stirring	2

Question	Answer	Marks
3(a)	$3V_X \approx V_{XY}$ <u>and</u> recorded to at least 1 dp <u>and</u> < 4.0 V	**1**
3(b)	$I_X \approx I_{XY}$ <u>and</u> recorded to at least 2 dp <u>and</u> < 1.00 A	**1**
3(c)(i)	A, V, Ω	**1**
3(c)(ii)	statement matching results <u>and</u> 'currents the same within limits of experimental accuracy' / owtte	**1**
3(d)(i)	correct calculations of R	**1**
	consistent 2 or consistent 3 sig figs	**1**
3(d)(ii)	R_Y and R_Z both within 10% of 10 (Ω)	**1**
3(e)	3 resistors in parallel arrangement <u>and</u> circuit symbols correct	**1**
	voltmeter and ammeter in correct arrangement <u>and</u> circuit symbols correct	**1**
3(f)	I_P and V_P present	**1**
	$R_P < R_X$	**1**

Question	Answer	Marks
4	**MP1 Apparatus** metre rule / measuring tape	1
	MP2 Method drop ball from measured height measure height of bounce repeat for different height of release	1
	MP3 Precaution any one from: • repeat (for each height of release) <u>and</u> average • measure to same part of ball each time • measure height of bounce at eye level • release without throwing/impeding • use of video (for height of bounce)	1
	MP4 Control variable any one from: • same (diameter/mass/material) ball • type of floor covering	1
	MP5 Table columns for release height and bounce height and <u>units</u>	1
	MP6 Analysis any one from: • suitable analysis of readings • draw a suitable graph of drop height against bounce height	1
	MP7 Additional point any one from: • additional control variable • at least 5 sets of data taken • repeat experiment for different diameter of ball/floor covering • automatic release to eliminate differences	1